

Application: Wipe on with a cloth, natural bristle brush, foam brush, paint pad applicator, or spray

\*Spraying Arm-R-Seal:

Arm-R-Seal can be sprayed successfully, but we prefer hand application methods because it is very easy to spray too much in one area. If you choose to spray, use very thin coats and watch for runs (large drips that run down the side of your project). If you notice a run, immediately wipe or brush it out. If you correct a run promptly, you will not see a mark. However, dried runs can be difficult to remove.

Important: Wear a mask and work in a well ventilated spray booth. Size: Small Needle Nozzle (1mm)

**WARNING: TEST FOR COMPATIBILITY WHEN USING THIS PRODUCT WITH PRODUCTS FROM OTHER BRANDS.** General Finishes products should be tested to your complete satisfaction before using. General Finishes will not be responsible for any failure if our products are used in conjunction with other brands of finishes. We do not test General Finishes products with those of another manufacturer and will not accept liability if there is a compatibility issue.

**WATER SPILLS AND DAILY USE:** Clean water spills up as they occur during regular use and protect from heat. Although General Finishes products are water resistant, they are not impervious to water. Surfaces will not be damaged by spilled water so long as it is cleaned up promptly. We recommend using coasters to protect your wood from standing water and pot holders to protect from heat.